



Break Strength Comparisons

GatorSTRAP® / GatorLASH® / MakoSTRAP® vs. Steel Strapping

Regular Duty Steel Strapping			GatorSTRAP®			MakoSTRAP®		
Width:	Thickness:	Average Strength:	Width:	Item ID:	*Break Strength:	Width:	Item ID:	*Break Strength:
5/8"	0.020	1,460 lbs.	5/8" MD	2015	1,500 lbs.	5/8"	5050	1,400 lbs.
5/8"	0.023	1,670 lbs.	5/8" MD	2015	1,500 lbs.	1"	5065	2,000 lbs.
3/4"	0.023	2,000 lbs.	5/8" HD	2010	2,000 lbs.	1"	5065	2,000 lbs.
3/4"	0.028	2,300 lbs.	3/4" MD	2070	2,400 lbs.	1"	5070	2,700 lbs.
High Tensile Steel Strapping			GatorSTRAP® / GatorLASH®			MakoSTRAP®		
Width:	Thickness:	Average Strength:	Width:	Item ID:	*Break Strength:	Width:	Item ID:	*Break Strength:
5/8"	0.020	1,810 lbs.	5/8" HD	2010	2,000 lbs.	1"	5065	2,000 lbs.
5/8"	0.023	2,450 lbs.	3/4" MD	2070	2,400 lbs.	1"	5070	2,700 lbs.
3/4"	0.020	2,000 lbs.	5/8" HD	2010	2,000 lbs.	1"	5065	2,000 lbs.
3/4"	0.023	2,300 lbs.	3/4" MD	2070	2,400 lbs.	1"	5070	2,700 lbs.
3/4"	0.025	2,620 lbs.	3/4" HD	2025	2,700 lbs.	1"	5070	2,700 lbs.
3/4"	0.029	3,050 lbs.	1-1/4"	2040	3,800 lbs.	1-1/4"	5080	3,500 lbs.
3/4"	0.031	3,250 lbs.	1-1/4"	2040	3,800 lbs.	1-1/4"	5080	3,500 lbs.
1-1/4"	0.020	3,825 lbs.	1-1/4"	2040	3,800 lbs.	1-1/4"	5080	3,500 lbs.
1-1/4"	0.025	4,780 lbs.	1-1/2" MD	2060	4,700 lbs.			
1-1/4"	0.029	5,250 lbs.	1-1/2" HD	2055	5,400 lbs.			
1-1/4"	0.031	5,450 lbs.	1-1/2" HD	2055	5,400 lbs.			
1-1/4"	0.035	5,800 lbs.	1-1/2" HD	2055	5,400 lbs.			

* All Break Strengths are Nominal +/-5%

Allegheny Industrial Associates

311 Plus Park Blvd, Suite 220 Nashville, TN 37217

(800) 444-6337 www.aiateam.com



You Ship It. We Protect It.™